

Table 5-12. Recommended Underclothing Based on Water Temperature

	Underwear			Liner		
	Rotary Wing	Fixed Wing Non-Ejection Seat	Fixed Wing Ejection Seat	Rotary Wing	Fixed Wing Non-Ejection Seat	Fixed Wing Ejection Seat
Water Temperature Above 60 degrees F	CWU-43 and CWU-44 or MCP Silkweight or MCP Midweight	CWU-43 and CWU-44 or MCP Silkweight or MCP Midweight	CWU-43 and CWU-44 or MCP Silkweight or MCP Midweight	Optional	Optional	Optional
Water Temperature 50 to 60 degrees F	CWU-43 and CWU-44 or MCP Silkweight and/or MCP Midweight	CWU-43 and CWU-44 or MCP Silkweight and/or MCP Midweight	CWU-43 and CWU-44 or MCP Silkweight and/or MCP Midweight	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P or MCP Heavyweight	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P
Water Temperature Below 50 degrees F	CWU-43 and CWU-44 (two sets) or MCP Silkweight and MCP Midweight	CWU-43 and CWU-44 (two sets) or MCP Silkweight and MCP Midweight	CWU-43 and CWU-44 (two sets) or MCP Silkweight and MCP Midweight	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P or MCP Heavyweight	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P	CWU-23/P or CWU-72/P or CWU-81/P and CWU-82/P
Note: For proper anti-exposure protection, a CWU-86/P or CWU-87/P Flyers' Anti-Exposure Coveralls must be worn over the recommended underclothing.						